



AUSTRALIAN TEST REPORT

For

Foshan City Shunde District Oukai Electrical Technology Co., LTD

Imitation ecological mosquito control system

Test Model: H-X5-TYN(APP)

Additional Models : please refer to Model list

Prepared for : Foshan City Shunde District Oukai Electrical Technology Co., LTD
Address : No 8, Huakou Huafa Rd, Ronggui Town, Shunde District, Foshan City, Guangdong Province, China

Prepared by : Ningbo LCS Standard Technology Service Co., Ltd.
Address : Room 101-106/202-206, Building 037, No. 166, Jinghua Road, Meixu Street, Ningbo High-tech Zone, Yinzhou District, Ningbo, Zhejiang, China

Tel : (0574) 8790 8011
Fax : (0574) 8790 6976
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : August 27, 2025
Number of tested samples : 1
Serial number : Prototype
Date of Test : August 27, 2025 - September 04, 2025
Date of Report : September 04, 2025



AUSTRALIAN TEST REPORT**AS/NZS CISPR 14.1:2021**

EMC - Requirements for household appliances, electric tools and similar apparatus Part 1: Emission

Report Number..... : LCSE08195022E

Date of Issue..... : September 04, 2025

Testing Laboratory Name..... : Ningbo LCS Standard Technology Service Co., Ltd.Address..... : Room 101-106/202-206, Building 037, No. 166, Jinghua Road,
Meixu Street, Ningbo High-tech Zone, Yinzhou District, Ningbo,
Zhejiang, ChinaTesting Procedure..... : Full application of Harmonised standards ☒
Partial application of Harmonised standards ☐
Other standard testing method ☐**Applicant's Name..... : Foshan City Shunde District Oukai Electrical Technology Co., LTD**Address..... : No 8, Huakou Huafa Rd, Ronggui Town, Shunde District, Foshan
City, Guangdong Province, China**Test Specification:**

Standard..... : AS/NZS CISPR 14.1:2021

Test Report Form No..... : TRF-4-E-021 A/0

TRF Originator..... : Ningbo LCS Standard Technology Service Co., Ltd.

Master TRF..... : Dated 2019-03

Ningbo LCS Standard Technology Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Ningbo LCS Standard Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Ningbo LCS Standard Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Equipment Under Test..... : Imitation ecological mosquito control system

Trademark..... : GOKDA

Test Model/Type..... : H-X5-TYN(APP)

Rating..... : Input: DC 11.1V, 8-12W

Results : PASS**Compiled by:**

Lorrain Li / Engineer

Supervised by:

Wen Li / Technique Director

Approved by:

Feng Liang / Manager



Ningbo LCS Standard Technology Service Co., Ltd.

Room 101-106/202-206, Building 037, No. 166, Jinghua Road, Meixu Street, Ningbo High-tech Zone, Yinzhou District, Ningbo, Zhejiang, China

Tel: +(0574) 8790 8011 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com.

Scan code to check authenticity.

EMC - TEST REPORT

Test Report No.....: LCSE08195022E

Applicant.....:	Foshan City Shunde District Oukai Electrical Technology Co., LTD
Address.....:	No 8, Huakou Huafa Rd, Ronggui Town, Shunde District, Foshan City, Guangdong Province, China
Telephone.....:	/
Fax.....:	/
Manufacturer.....:	Foshan City Shunde District Oukai Electrical Technology Co., LTD
Address.....:	No 8, Huakou Huafa Rd, Ronggui Town, Shunde District, Foshan City, Guangdong Province, China
Telephone.....:	/
Fax.....:	/
Factory.....:	Foshan City Shunde District Oukai Electrical Technology Co., LTD
Address.....:	No 8, Huakou Huafa Rd, Ronggui Town, Shunde District, Foshan City, Guangdong Province, China
Telephone.....:	/
Fax.....:	/

The applicant and manufacturer information, product name, model, trademark and other information in this report are all provided by the applicant, and this laboratory is not responsible for verifying its authenticity.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



ENVIRONMENTAL CONDITIONS

The climatic conditions during the test are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. the climatic conditions during the test were in the following Limits:

Ambient temperature	15°C - 30°C
Relative Humidity air	30% - 60%
Atmospheric pressure	86 kPa - 106 kPa

Climate values will be recorded and recorded separately if specifically required in the base standard or application product/product series standard.

POSSIBLE TEST CASE VERDICTS

Test cases does not apply to test object	N/A
Test object does meet requirement	P(Pass) / PASS
Test object does not meet requirement	F(Fail) / FAIL
Not measured	N/M

DEFINITION OF SYMBOLS USED IN THIS TEST REPORT

☒ Indicate that the conditions, standards or equipment listed is applicable to this report / test / EUT.
☐ Indicate that the conditions, standards or equipment listed is not applicable to this report / test / EUT.

REVISION HISTORY

Revision	Issue Date	Revision Content	Revised by
000	September 04, 2025	Initial Issue	-

Remark:
000) : “---”



TABLE OF CONTENTS

1. GENERAL INFORMATION	6
1.1. General Description of The Item(s).....	6
1.2. Operating Mode(s) Used of Tests	7
1.3. Support / Auxiliary Equipment For The EUT	7
1.4. Description of Test Facility	7
2. STATEMENT OF THE MEASUREMENT UNCERTAINTY	8
3. MEASURING DEVICES AND TEST EQUIPMENT	9
4. VERDICT SUMMARY SECTION	10
4.1. Standard(s).....	10
4.2. Overview of Results	10
5. EMISSION TESTS	11
5.1. Radiated Disturbance	11
ANNEX A - TEST RESULTS	12
ANNEX B - TEST PHOTOS	14
ANNEX C - EXTERNAL AND INTERNAL PHOTOS OF THE EUT	15



1. GENERAL INFORMATION

1.1. GENERAL DESCRIPTION OF THE ITEM(S)

Equipment Under Test	Imitation ecological mosquito control system
Test Model/Type	H-X5-TYN(APP)
Additional Models/Type	See Model list
Description of Model difference	-
Rating	Input: DC 11.1V, 8-12W
Highest internal frequency (Fx)	≤ 15 MHz

Model	PCB	Rating	Series
H-X5-TYN(APP)	Same PCB layout	Input: DC 11.1V, 8-12W	1
H-X5-TYN			

The applicant states:

- All models use the same circuit and PCB layout, only the appearance is different.
- This report after information review and verification, the model “H-X5-TYN(APP)” were chosen as the representative model to perform all the tests.



1.2. OPERATING MODE(S) USED OF TESTS

During the tests, the following operating mode(s) has(have) been used.

Operating Mode	Operating Mode description	Used for testing
1	Working&Charging	☒
2	High	☐
3	Low	☐
4	Full load	☐

1.3. SUPPORT / AUXILIARY EQUIPMENT FOR THE EUT

EUT has been tested using the following auxiliary equipment :

Auxeq	Model/Type	Manufacturer	Supplied by
--			

1.4. DESCRIPTION OF TEST FACILITY

Test Location 1	Ningbo LCS Standard Technology Service Co., Ltd. Room 101-106/202-206, Building 037, No. 166, Jinghua Road, Meixu Street, Ningbo High-tech Zone, Yinzhou District, Ningbo, Zhejiang, China CNAS Registration Number is L13445.
Date of receipt of test item	August 27, 2025
Date(s) of performance of test	August 27, 2025 - September 04, 2025



2. STATEMENT OF THE MEASUREMENT UNCERTAINTY

The data and results referenced in this document are true and accurate. the reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. the measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods - Part 4: Uncertainty in EMC Measurements" and is documented in the LCS quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. the manufacturer has the sole responsibility of continued compliance of the device.

Measurement	Uncertainty (U_{lab})	Uncertainty (U_{cisp})
Radiated disturbance (30MHz - 200MHz)	± 3.48 dB	± 5.3 dB
Radiated disturbance (200MHz - 1GHz)	± 3.48 dB	± 5.3 dB

Supplementary information:

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.



3. MEASURING DEVICES AND TEST EQUIPMENT

RADIATED DISTURBANCE (30MHz - 1GHz)						
Item	Test equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	AUDIX	E3	N/A	/	/
2	3m Semi Anechoic Chamber	MAORUI	9m*6m*6	160218849	2024-04-11	2027-04-10
3	By-log Antenna	SCHWARZBECK	VULB9168	9168-988	2025-04-13	2026-04-12
4	Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-2049	2025-05-17	2026-05-16
5	EMI Test Receiver	R&S	ESRP	101372	2025-05-09	2026-05-08
6	AMPLIFIER	SCHWARZBECK	BBV9745	136	2025-05-09	2026-05-08
7	RF Cable	Hubber Suhner	CBL-RE	/	/	/
8	AMPLIFIER	SCHWARZBECK	BBV9718C	21	2025-05-09	2026-05-08



4. VERDICT SUMMARY SECTION

This chapter present an overview of the standards and results. Refer the next chapter for details of measured test results and applied test levels.

4.1. STANDARD(S)

AS/NZS CISPR 14.1:2021 - Electromagnetic compatibility - Requirements for household appliances, electric tools and similar apparatus Part 1: Emission.

4.2. OVERVIEW OF RESULTS

EMISSION TESTS - AS/NZS CISPR 14.1		
Requirement - Test case	Limit	Verdict
Conducted Disturbance - Mains ports	Table 5, Table 6	N/A
Conducted Disturbance - Auxiliary ports	Table 5	N/A
Disturbance power in the frequency range 30 MHz to 300MHz ¹	Table 7	N/A
Radiated Disturbance in the frequency range 30 MHz to 1 GHz ¹	Table 9	PASS
Discontinuous Disturbances - Click	Clause 4.2.2	N/A

Supplementary information :

The EUT shall be assessed for emissions in the frequency range from 30 MHz to 1 000 MHz by testing in accordance with either method 1) or 2).

- 1) The limits for radiated disturbances in Table 9 for the selected test method shall be met.
- 2) The EUT shall be met disturbance power limits, But the EUT shall be also deemed to comply with the requirement of this document in the frequency range from 300 MHz to 1 000 MHz without further testing if both conditions below are fulfilled:
 - the disturbance power emission from the EUT is lower than the limits of Table 7 reduced by the values of Table 8;
 - the maximum clock frequency is less than 30 MHz.



5. EMISSION TESTS

5.1. RADIATED DISTURBANCE


Standard	AS/NZS CISPR 14.1:2021
Basic Standard(s)	CISPR 16-2-3
Test method	Semi Anechoic Chamber (SAC)

SAC Radiated disturbance limit in the frequency range 30 MHz - 1000 MHz

Frequency range [MHz]	Limit: Quasi-peak [dB(μV/m)]		IF BW
	3 m distance	10 m distance	
30 - 230	40	30	120 KHz
230 - 1000	47	37	

1) At the transition frequency, the lower limit applies.

Test configuration



Test Procedure Description

The radiated disturbance test was conducted in a 3m Semi Anechoic Chamber and conforming to CISPR 16-2-3. the EUT is placed on a turntable, which is 0.8 meter high above the ground. the turntable can rotate 360 degrees to determine the position of the maximum emission level. the EUT is set 3 meters away from the receiving antenna, which is mounted on an antenna tower. the antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Log-periodic antenna or horn antenna is used as a receiving antenna. both horizontal and vertical polarization of the antenna is set on test.


Test Results refer to Annex A.1



ANNEX A - TEST RESULTS

A.1. RADIATED DISTURBANCE TEST RESULTS

Environmental Conditions	25.9°C, 58% RH
Model	H-X5-TYN(APP)
Operating mode	Mode 1 (worst case)
Test voltage	DC 18.68V
Test engineer	Xi Ouyang
Pol	Vertical



Site : 3m chamber

Condition : AS/NZS CISPR 14.1 3m VULB9168 NB 4 VERTICAL

		Read	Cable	Antenna	Preamp		Limit	Over	
	Freq	Level	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	39.99	33.52	2.26	14.00	30.20	19.58	40.00	-20.42	QP
2	59.65	34.15	2.57	12.63	30.22	19.13	40.00	-20.87	QP
3	153.20	33.75	3.58	14.12	30.36	21.09	40.00	-18.91	QP

Note: 1. All Levels are Quasi-peak values.

2. Level= Read Level + Antenna Factor + Cable Loss - Preamp Factor

3. The emission that are 20dB below the official limit are not reported




Ningbo LCS Standard Technology Service Co., Ltd.

Room 101-106/202-206, Building 037, No. 166, Jinghua Road, Meixu Street, Ningbo High-tech Zone, Yinzhou District, Ningbo, Zhejiang, China

Tel: +(0574) 8790 8011 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com.

Scan code to check authenticity.

Environmental Conditions	25.9°C, 58% RH
Model	H-X5-TYN(APP)
Operating mode	Mode 1 (worst case)
Test voltage	DC 18.68V
Test engineer	Xi Ouyang
Pol	Horizontal



Site : 3m chamber

Condition : AS/NZS CISPR 14.1 3m VULB9168 NB 4 HORIZONTAL

	Freq	Read	Cable	Antenna	Preamp	Limit	Over	Remark
		Level	Loss	Factor	Factor		Limit	
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB
1	37.68	33.29	2.22	13.67	30.20	18.98	40.00	-21.02 QP
2	49.19	32.96	2.40	13.40	30.20	18.56	40.00	-21.44 QP
3	145.35	33.98	3.50	13.34	30.35	20.47	40.00	-19.53 QP

Note: 1. All Levels are Quasi-peak values.

2. Level= Read Level + Antenna Factor + Cable Loss - Preamp Factor

3. The emission that are 20db below the official limit are not reported



Ningbo LCS Standard Technology Service Co., Ltd.


Room 101-106/202-206, Building 037, No. 166, Jinghua Road, Meixu Street, Ningbo High-tech Zone, Yinzhou District, Ningbo, Zhejiang, China

Tel: +(0574) 8790 8011 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com.

Scan code to check authenticity.

ANNEX B - TEST PHOTOS

B.1. Radiated Disturbance



ANNEX C - EXTERNAL AND INTERNAL PHOTOS OF THE EUT

The photographs show the equipment under test.



Figure. 1 (H-X5-TYN(APP))



Figure. 2 (H-X5-TYN(APP))





Figure. 3 (H-X5-TYN(APP))




Figure. 4 (H-X5-TYN(APP))






Figure. 5 (H-X5-TYN(APP))



Figure. 6 (H-X5-TYN(APP))





Figure. 7 (H-X5-TYN(APP))




Figure. 8 (H-X5-TYN(APP))






Figure. 9 (H-X5-TYN(APP))



Figure. 10 (H-X5-TYN(APP))






Figure. 11 (H-X5-TYN(APP))




Figure. 12 (H-X5-TYN(APP))






Figure. 13 (H-X5-TYN(APP))




Figure. 14 (H-X5-TYN(APP))






Figure. 15 (H-X5-TYN(APP))

----- END -----

